Product data sheet


MACARON 1 POST TOP LUMINAIRES
MC-20012-W-W40
LIGMAN



IP 66 IK 08

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Life time L90B10 Ta 25° 25,000 - Life time L80B10 Ta 50° 50,000 - Die-cast aluminium housing and frame pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - High-efficiency PMMA lens - Durable silicone rubber gasket - Clear toughened glass lens

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	104 W	CRI	80
Total flux	11278 lm	LOR	100%
Luminous efficacy	108 lm/W	ULOR	100%
		Total power	104 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 19.69 in
Diameter: 19.69 in
Weight: 10 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 104 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 08
Surface temperature: 40°C