



Product data sheet

7700 FOCO L LED FLOODLIGHT
7700 6403AB (77000 0085)
SCHUCH



LED floodlight, FOCO L, 140 W, 20000 lm, 143 lm/W, Class I, IP66, asymmetrical wide beam, 4000 K, CRI \geq 70, Ta -40 °C/+40 °C, L90>100000 h (@ Ta max), Pane Safety glass clear, Housing Die-cast aluminium, Colour grey, DB702N. LED floodlight FOCO L of the GreenLine series with outstanding sustainable product design. Consisting of powder-coated die-cast aluminium housing, two-part. Upper part with LED modules, lower part with ECG, tempered safety glass pane, cable entry and strain relief, hinged. Zhaga LED modules, direct beam, Multi-Layer Technology. ECG with high surge protection, overload and short circuit protection. Mounting bracket with swivel range of 180°. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 573,00 mm, Width/Diameter 360,00 mm, Height 100,00 mm, Net weight 9,70 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	140 W	CRI	70
Total flux	19998 lm	LOR	100%
Luminous efficacy	143 lm/W	ULOR	7%
		Total power	140 W

Mounting mode

Pole top mounted, Wall mounted

Shape and measurements

Length: 22.56 in
Width: 14.17 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 140 W
Appliance Class: I

Protection

IP: 66
IK: 10
Designation labels: CE