Product data sheet


CEILING AND WALL MOUNTED PURELITE SLIM 14W 1840LM CRI > 80 3000K DALI2
2004.4890 - PURLT S CW781X62 LED1840-830 DALI
REGENT



IP 20 IK 08

Ceiling and wall mounted Purelite Slim with LED, system power: 14 W, standby power 0.5 W, luminous flux of luminaire 1840 lm, colour rendering index CRI > 80, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 75'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, omni-directional, incl. illumination of the ceiling, housing in aluminium, natural-colour anodised diffuser in synthetic material opal, 1 integral control gear, DALI2, protection class I, ingress protection IP20, glow wire test 650 °C, impact strength: IK 08, this product contains a light source of energy efficiency class B and EPREL registration number: 1564303 L = 781 mm, B = 62 mm, H = 35 mm

Light output 1



1 x LED

Nominal lamp power	10.9 W	LOR	100%
Lamp flux	1840 lm	ULOR	10%
Luminous efficacy	169 lm/W	Total flux	1840 lm
CCT	3000 K	Total power	14 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 30.75 in
Width: 2.44 in
Height: 1.38 in
Weight: 1.81 kg

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 14 W
Appliance Class: I

Protection

IP: 20
IK: 08