## Product data sheet

VOLKMAR II (WALL FITTING) 9.840.0088.05

LEIPZIGER LEUCHTEN






CRI

CRI




For medium light requirements, mounting heights from 3.00 - 4.00 m. - Luminaire body made of aluminium/galvanized steel sheet - Impact-resistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL - or DB -colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

## Light output 1



1 x High pressure mercury	vapour lamp
Nominal lamp power	125 W
Lamp flux	6800 lm
Luminous efficacy	42 lm/W
CCT	3400 K

LOR	85%
ULOR	28%
Total flux	5755 lm
Total power	137 W



## 1 x High pressure mercury vapour lampNominal lamp power80 WLamp flux4000 lmLuminous efficacy38 lm/WCCT3400 K

LOR	88	5%
ULOR	28	3%
Total flux	3385	lm
Total power	89	W

Mounting mode

Wall mounted

Shape and measurements

Height: 16.14 in Diameter: 16.14 in Electric

54

54

System power: 89-137 W

Protection

IP: 55