Product data sheet

X-LINE SLIGHT SPOTS LOW UGR L-DOWN LED 2400 LOUVER E / 2X 600 15° E 24 840 / L-1600MM S-1,5M TWO CIRCUIT 19.4400.232E.24


LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - anodised aluminum. Dimensions: 1600 x 34 x 68 mm. Diffuser: LOUVER (anti-glare louver) / optical system based on PMMA lenses. The efficiency of the optical system is 71,66%. Beam angle: (C0-C180) / (C90-C270) - 46° / 44,6° // (C0-C180) / (C90-C270) - 17,8° / 19,8°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 100000 h L80/B10. Luminaire luminous flux: 1781 / 1054 lm. Power of luminaire: 14,3 / 10,8 W. Luminaire's light efficiency: 124,5 / 97,6 lm/W. Driver: standard on/off (E) / standard on/off (E). Voltage 220..240 V, 50..60 Hz. Circuit load capacity: 11 (B10), 17 (B16), 16 (C10), 27 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



4 x LED

Nominal lamp power	3.575 W	LOR	52%
Lamp flux	622 lm	Total flux	1305 lm
Luminous efficacy	174 lm/W	Total power	14.3 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 62.99 in
Width: 1.34 in
Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 14.3 W
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F