


# Product data sheet

HIGH5 TYPE I GREY 18W 3000K RA>70  
8246087889  
SG ARMATUREN



Design: Christian Hvidt Mast top-mounted LED luminaire. IP66. LED luminaire. Base and top made of die-cast aluminium, front made of tempered glass. Base and diffuser in textured light grey. Direct lens optical solutions (Multilens). Complete with LED driver for operation of LED light sources mounted to component rail with internal connector/lampholder and pre-mounted with six-metre connection cable. Prepared for mounting on 60 mm mast. Safety class II. Light distribution Type I Light technic LED 18W 3000K Ra>70 SDCM 4 L80/B10 >80,000 hrs at Ta=25°C Control/Dimming On/Off Protection Class II IP66 IK08 Energy and approvals A++ CE Materials and finish Housing: Die-cast aluminium Colour: Grey (structure 2150 sablé) Optics: Glass Mounting/Connection Post - top (Ø60mm), Outdoor Cable 2x1mm² 6m Wind projected area: 385cm² - Max 4.2 kg Max. luminaires per circuit breaker: B10: 32, B16: 50, C10: 52, C16: 85

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	18 W	CRI	70
Total flux	2080 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	18 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 17.52 in

Width: 6.67 in

Height: 7.68 in

## Adjustability

Fixed

## Electric

System power: 18 W

Appliance Class: II

## Protection

IP: 66

IK: 08