Product data sheet

SYSTEM BATTEN LUMINAIRE SLASH 2 HPE (HIGH PERFORMANCE EFFIC
2006.4019 - SLASH2 INS2938 HPE LED4400-830 DALI
REGENT



IP 20

System batten luminaire Slash 2 HPE (High Performance Efficiency), for mounting in support profile Slash 2, with LED, system power: 40 W, standby power 0.5 W, luminous flux of luminaire 4400 lm, colour rendering index CRI > 80, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, 1 integral control gear, DALI, all-round beam, white powder coated, pre-wired batten luminaire with rapid connection ICT-Instant Contact Technology, support profile and system components to be ordered separately non-renewable, in 2 parts, with ICT protection class I, ingress protection IP20, this product contains a light source of energy efficiency class B and EPREL registration number: 1249142 L = 2938 mm, B = 41 mm, H = 35 mm

Light output 1



1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	4650 lm	Total flux	4650 lm
Luminous efficacy	232 lm/W	Total power	43 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	4400 lm	Total flux	4400 lm
Luminous efficacy	220 lm/W	Total power	40 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 115.59 in
Width: 1.89 in
Height: 2.76 in
Weight: 6.338 kg

Electric

System power: 40-43 W
Appliance Class: I

Protection

IP: 20

Adjustability

Fixed

Design

Color of housing: White