


# Product data sheet


LED VALUE PANEL 0606B 36W 830 H DALI  
4058075755185  
LEDVANCE



IP  
20

Latest backlit LED technology platform. Available in 3 standard metric sizes: 600x600, 300x1200, 600x1200mm. Standard CCT: 4000K, 6500K & 3000K. High color rendering: CRI > 80. High power factor: PF>0.90. Recess mount with optional plaster ceiling mounting. clips and suspension kit. Flicker free driver. EMC suppression circuit in driver. Sturdy SPCC housing. Safety compliance certificates: CB. EU RoHS 2.0 compliant. DALI DIM version available. Integrated heat resistance lens for uniform light distribution, reduce product height to only 34mm. Long 50,000hr lifetime reduces maintenance costs. Fast connector between panel and driver for easy installation and maintenance. Seamless aluminum frame elegant design. IP40, IP54 protection from diffuser side suitable for different installations.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	36 W	CRI	80
Total flux	3680 lm	LOR	100%
Luminous efficacy	102 lm/W	Total power	36 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Length: 21.77 in

Width: 21.77 in

Height: 0.39 in

## Adjustability

Fixed

## Electric

System power: 36 W

## Protection

IP: 20