


Product data sheet

AME LED M3 LSTR
AMELED WIRELESS EMERGENCY
DEXTRA




AME LED LSTR - IP65, IK07. Maintained 3hr emergency luminaire, robust polycarbonate body and lens, white finish with clear reeded diffuser. Compatible with Self Test wireless reporting for the Reacta-Link system. 395 Luminaire Lumen output in Emergency mode. Options: AME ELK - Emergency Legend Kit AME ELK ISO - Emergency Legend kit ISO 7010

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.4 W	CRI	80
Total flux	444 lm	LOR	100%
Luminous efficacy	69 lm/W	ULOR	4%
		Total power	6.4 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.4 W	CRI	80
Total flux	395 lm	LOR	100%
Luminous efficacy	62 lm/W	ULOR	4%
		Total power	6.4 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 14.57 in

Width: 5.51 in

Height: 3.54 in

Adjustability

Fixed

Electric

System power: 12.8 W

Ballast: ECG

Information regarding emergency functions

Supplementary emergency lighting

Emergency power supply: Single battery 3 h

Emergency sign: N/A

Protection

IP: 65

IK: 07

Designation labels: CE