Product data sheet


RING OF FIRE
311670.004.1
RZB



IP 20 IK 02

Series: Ring of Fire Type of Protection: IP 20 Protection Class: I Voltage: 230 V / 50 Hz Supporting ring: anodised aluminium. Hand-blown opal glass, satin finish. Inner circle surface: anodised aluminium. Suspension rod: Ø 30 mm, 196 mm long, anodised aluminium. Canopy: anodised aluminium, Ø 221, 36 mm high. LED included. Available Colours: anodised aluminium Type of Installation: Pendant Dimensions: D 495, H 55 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 2550lm System power: 24W Beam Angle: 115° Number of fittings B10A: 12 Number of fittings B16A: 20 Inrush current: 30A Unified Glare Ratio: 22,8 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	24 W	CRI	80
Total flux	2550 lm	LOR	100%
Luminous efficacy	106 lm/W	ULOR	44%
		Total power	24 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 2.36 in
Diameter: 19.49 in

Adjustability

Fixed

Electric

System power: 24 W

Protection

IP: 20
IK: 02