



# Product data sheet

LD141Y 4.4W 350MA WB  
LD141Y-E3-350-WB  
LIGHTGRAPHIX



LD141Y Ø64mm Recessed Wall Light. IP67. Constant Current. 4.4W 350mA 34° Wide beam. The LD141 has been designed for exterior applications and can be specified as an uplight (LD141X) or wall light (LD141Y). Compact in size, the fittings offer a powerful output with a large range of features. The E3 engine delivers a high output of 567 lumens and beam angles ranging from a 12° narrow to a 15° x 49° extra oval beam. There is also the ability to specify a 20° tilt film to angle the light down onto the lit surface for a more concentrated effect. Designed with a repairable light engine, glare and fixing accessories, the LD141X offers a circular, low glare, solution for a range of exterior rated applications.

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4.4 W	CRI	85
Total flux	380 lm	LOR	100%
Luminous efficacy	86 lm/W	ULOR	100%
		Total power	4.4 W

## Mounting mode

Wall recessed

## Shape and measurements

Height: 2.52 in  
Diameter: 2.52 in

## Adjustability

Fixed

## Design

Material impression: Matt, Bronze, Glass, Brass, Gloss, Stainless steel  
Color of housing: Black, White, Anthracite / graphite, Silver gray

## Electric

System power: 4.4 W  
Controller: Dimmable 0..10V, Dimmable 1..10V, DMX, DALI  
Appliance Class: III

## Protection

IP: 67  
IK: 06  
Designation labels: CE

## Other operating numbers

Ambient temperature range: -4...122°F