Product data sheet

MORITZ II (1-ARMED) 9.117.3162.02

LEIPZIGER LEUCHTEN









Mounting height of 4.50 to 6.00 m for medium or high light requirements - Luminaire made of cast aluminium, varnished - Superior lighting due to computer-optimised reflector system for sodium vapour high pressure discharge with clear glass tube bulb - Cover of single-pane safety glass, hinged - Cable protection hosing made of braided stainless steel - All electrical parts fitted -Available in any required RAL or DB colour without extra price - Special Ø102 mm pole for 4.50 m mounting height, Ø114 mm pole for 6.00 m mounting height, including pole mounting hot-dip galvanised and varnished are part of the delivery Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure mercury vapour lamp		
Nominal lamp power	125 W	
Lamp flux	6800 lm	
Luminous efficacy	41 lm/W	
CCT	3400 K	
CRI	54	

LOR	82%
Total flux	5579 lm
Total power	137 W



1 x High pressure mercury vapour lamp			
Nominal lamp power	80 W	LOR	
Lamp flux	4000 lm	Total flux	
Luminous efficacy	37 lm/W	Total power	
CCT	3400 K		
CRI	54		

Mounting mode

Pole top mounted

Shape and measurements

Length: 21.26 in Width: 21.26 in Height: 6.89 in Electric

System power: 89-137 W

Protection

IP: 55

82% 3282 lm 89 W