

Product data sheet


URBANO LED PLUS VERSION 302W 36950LM 2200K IP66 O65 - FOR EXPRESS ROADS GRAPHITE II TILT ADJUSTMENT (P.. 130195.3L57.225

LUG



Professional streetlight luminaire for LED light sources. Mounting: on pillar $\varnothing 60/76\text{mm}$, on outriggers $\varnothing 60/76\text{mm}$ Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0.050 m^2 Power supply efficiency $>93\%$ Power: 220-240V 50/60Hz Lifetime LED (L90): 100 000 h Available on request: DIM 1..10V, LLOC, twilight sensor, 10kV surge protection Additional information: Tilt adjustment: 5° , knife switch (for protection class I), access to the driver chamber without the use of tools, NTC. The possibility of using one or more power supplies in the luminaire. CRI/Ra >70 Additional equipment: additional anti-corrosive protection (index extension: .985) Other remarks: the pole and boom are not part of the luminaire Warranty: 5 years Application: freeways, express roads, local roads, town roads, residential area roads, area lighting, airports, parking areas. Type of optics: O65 - for express roads

Light output 1 (integrated)



Lamp type	LED	CCT	2200 K
Nominal lamp power	302 W	CRI	70
Total flux	36950 lm	LOR	100%
Luminous efficacy	122 lm/W	Total power	302 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 35.04 in

Width: 15.35 in

Height: 4.37 in

Adjustability

Tiltable

Design

Color of housing: Anthracite / graphite

Electric

System power: 302 W

Controller: DALI

Appliance Class: II

Protection

IP: 66

IK: 08