Product data sheet

ECLDISPLAYCAS_WHITE

ECLDISPLAYCAS_2700K_WASH 1530DEG_MIN ZOOM


PROLIGHTS





EclDisplay is a range of revolutionary and flexible LED spotlights designed for galleries, retail and any public venue where an advanced but classical looking fixture is needed, with several control options, sources and optic versions available to precisely meet any application. The EclDisplay CAS is the version of the EclDisplay range made with integrated CASAMBI control on-board, leaving to System Integrators to install this luminaire in venues with their own wiring distribution and control. EclDisplay CAS includes a high-efficiency 25W single color LED available in 2700K, 3000K, 4000K and 5600K versions both in black and white finishing, and it is completed with a wide selection of optional zoomable profile or wash lenses, and other optical accessories like louvres and snoots, making it a truly a multi-purpose fixture. Main features: CASAMBI control on-board 25W single color LED available in 2700K, 3000K, 4000K and 5600K versions both in black and 5600K versions both in black and snoots, making it a truly a multi-purpose fixture. Main features: CASAMBI control on-board 25W single color LED available in 2700K, 3000K, 4000K and 5600K versions both in black and snoots.

Light output 1



1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI

33.6 W 1220 lm 36 lm/W 2794 K 90 LOR Total flux Total power

100% 1222 lm 33.6 W

Mounting mode

Ceiling mounted, Contact rail, Standing / Bollard

Shape and measurements

Length: 5.55 in Width: 3.35 in Height: 7.51 in

Adjustability

Rotatable, Tiltable, Free

Electric

System power: 33.6 W Controller: DMX, DALI Color adjustable Appliance Class: I

Protection

IP: 20 IK: 08 Surface temperature: 65°C Designation labels: CE