

Product data sheet


ECODISC II MIDI Ø 330 MM
40009912
PROLUMIA




IP
44

Light source: SMD 2835 LED Beam angle: 120° Color temperature switchable:3000K/4000K/6500K Light output: 1650Lm Operating temperature: -20°C - +40°C Rated life hours:> 30,000 LED driver (included): CE Input: 220-240V AC 50/60Hz Electrical safety class:Class I Power factor: > 0.90


Light output 1



1 x LED			
Nominal lamp power	18 W	LOR	100%
Lamp flux	1650 lm	Total flux	1650 lm
Luminous efficacy	92 lm/W	Total power	18 W
CCT	6500 K		
CRI	80		



1 x LED			
Nominal lamp power	18 W	LOR	100%
Lamp flux	1650 lm	Total flux	1650 lm
Luminous efficacy	92 lm/W	Total power	18 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	18 W	LOR	100%
Lamp flux	1650 lm	Total flux	1650 lm
Luminous efficacy	92 lm/W	Total power	18 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant, Wall mounted

Electric

System power: 18 W
Appliance Class: 0

Shape and measurements

Height: 2.60 in

Diameter: 12.99 in

Protection

IP: 44