Product data sheet

ECODISC II MIDI Ø 330 MM 40009912


PROLUMIA






Light source: SMD 2835 LED Beam angle: 120° Color temperature switchable:3000K/4000K/6500K Light output: 1650Lm Operating temperature: -20°C - +40°C Rated life hours:> 30,000 LED driver (included): CE Input: 220-240V AC 50/60Hz Electrical safety class:Class I Power factor: > 0.90

Light output 1




I x LED	
Nominal lamp power	18 W
Lamp flux	1650 lm
Luminous efficacy	92 lm/W
CCT	6500 k
CRI	80

LOR	100%
Total flux	1650 lm
Total power	18 W



1 x LED	
Nominal lamp power	18 W
Lamp flux	1650 lm
Luminous efficacy	92 lm/W
CCT	4000 K
CRI	80

LOR	100%
Total flux	1650 lm
Total power	18 W



1 x LED			
Nominal lamp power	18 W	LOR	100%
Lamp flux	1650 lm	Total flux	1650 lm
Luminous efficacy	92 lm/W	Total power	18 W
CCT	3000 K		
CRI	80		

Mounting mode

Pendant, Wall mounted

Electric

System power: 18 W Appliance Class: 0 Shape and measurements

Protection

Height: 2.60 in

Diameter: 12.99 in

IP: 44