Product data sheet


COLLEGE LED6500-840 HF L1500
96628877
THORN LIGHTING



IP 44 IK 05

A high performance, surface mounted, LED luminaire. Electronic, fixed output control gear. Class I electrical, IP44. Body: white painted steel. End caps: white polycarbonate with a curved, precision extruded clear prismatic polycarbonate diffuser. Ø21.5mm cable entry hole in the centre of the back spine with optional cable entry through each end cap. Fitting supplied with sealing grommets and innovative "quick fix" horseshoe and sliding washers for direct screw fixing to surface, fixing centres 1450mm. Standard BESA fixings. Can be suspended using wire suspension accessory kit (to be ordered separately). 3 x 2 x 2.5mm² piano key terminal block. Complete with 4000K LED Dimensions: 1520 x 217 x 90 mm Total power: 64 W Weight: 4.44 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	64 W	CRI	80
Total flux	6500 lm	LOR	100%
Luminous efficacy	102 lm/W	ULOR	5%
		Total power	64 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 59.84 in
Width: 8.54 in
Height: 3.54 in
Weight: 4.4 kg

Design

Color of housing: White

Electric

System power: 64 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 44
IK: 05
Designation labels: CE