


Product data sheet

LOUI 50
925322.0045.76
RZB




IP
20

IK
03

Series: LESS IS MORE 50;system Gerades Modulgehäuse Aluminium-Strangpressprofil pulverbeschichtet, stirnseitig offen zum weiter verdrahten zum Lichtbandsystem. Austauschbare und herausnehmbare LED-Einheit mit integriertem Betriebsgerät. Diffusor(en) aus vergilbungsfreiem Kunststoff (PMMA) opal. Nur optional: Lichtbandsystem vorbereitet für Seilabhängung! Colour: silver, matt (approx. RAL;9006) Length: 1961;mm Width: 57;mm Height: 75;mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 47;W Rated luminous flux: 5400;lm Luminous efficiency: 115;lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP;20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	47 W	CRI	80
Total flux	5400 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	47 W

Mounting mode

Ceiling mounted

Electric

System power: 47 W

Shape and measurements

Length: 2.24 m
Width: 0.077 m
Height: 0.0295 m

Protection

IP: 20
IK: 03

Adjustability

Fixed