

Product data sheet

RONDOS MINI
911415.002
RZB




IP
20

IK
06

Series: RONDOS mini Recessed projectors Housing: die-cast aluminium, powder-coated. Rotation range: 356°; swivel range: ±160/35°. Black plastic ring and recessed LED to prevent glare from the side. Optical assembly with lens made of plastic (polycarbonate) for the best homogeneous light distribution - can be changed without tools. Installation without tools thanks to spring fastening system. Including separate LED converter with connecting cable 600 mm. High quality converter without flickering and stroboscopic effect. Through-wiring box (5 pole) available as accessory. The following accessories can be mounted without use of tools: interchangeable lenses, honeycomb louvre, clear and frosted diffusers, white interchangeable plastic ring. Colour: traffic white, matt (RAL 9016) Diameter: 143 mm Height: 3 mm Cut-out diameter: 133 mm Recess height: 170 mm Luminaire: recess height: 120 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 85 System power: 19 W Rated luminous flux: 1700 lm Luminous efficacy: 89 lm/W Control gear: Regulated power supply Protection class: II Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	19 W	CRI	80
Total flux	1700 lm	LOR	100%
Luminous efficacy	89 lm/W	Total power	19 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.12 in
Diameter: 5.63 in

Adjustability

Rotatable, Tilttable

Electric

System power: 19 W

Protection

IP: 20
IK: 06