

# Product data sheet


MULTILUME HYDRO LED 300X1200 940 DALI  
23393-402  
FAGERHULT



IP  
65

Installation Recessed or surface mounted. The recessed model is suitable for fixed suspended ceilings or suspended ceilings with visible T-bars. Do not cover with insulation. For detailed information, see the installation instructions. Connection Connection in separate driver box. The driver box can be positioned next to the luminaire. Snap-in terminal block 3x1.5 mm<sup>2</sup> (when dimming 5x1.5 mm<sup>2</sup>). The surface mounted model has cable entries fitted with blanking grommets on the back and in each end-cap and snap-in terminal block. Design Luminaire body in extruded aluminium and enamelled sheet steel. Surface mounted model in white enamelled sheet steel (RAL 9016). Louvre Delta – microprismatic acrylic louvre (PMMA) above hardened 4 mm glass cover. Miscellaneous Recessed model IP 65 under suspended ceiling, IP 50 above. Surface mounted model IP 65.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	56 W	CRI	90
Total flux	6262 lm	LOR	100%
Luminous efficacy	112 lm/W	Total power	56 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 48.27 in

Width: 12.83 in

Height: 2.87 in

## Adjustability

Fixed

## Design

Color of housing: White

## Electric

System power: 56 W

## Protection

IP: 65