


Product data sheet

LINEDO_2,3M_90_1111
952390.D50.500.002
RZB




IP
54

IK
03


LINEDO D50, 120 W, 13800 lm, 950, aluminium, on/off Continuous line luminaire, L 2291 B 58 H 76

Light output 1 (integrated)




Lamp type	LED	CCT	5000 K
Nominal lamp power	30 W	CRI	90
Total flux	3450 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	30 W

Light output 2 (integrated)




Lamp type	LED	CCT	5000 K
Nominal lamp power	30 W	CRI	90
Total flux	3450 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	30 W

Light output 3 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	30 W	CRI	90
Total flux	3450 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	30 W

Light output 4 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	30 W	CRI	90
Total flux	3450 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	30 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in

Width: 90.20 in

Height: 2.99 in

Adjustability

Fixed

Electric

System power: 120 W

Protection

IP: 54

IK: 03