

Product data sheet


MIRAGE 3 165 ROUND ANTI-LIGATURE
MEDIUM WHITE
WHITECROFT




IP
44

See lamps to select output and colour variants MIRAGE 3 recessed downlighter white reflector, medium distribution. Narrow 11mm width bezel and shallow depth body. Graphite heat sink for optimum thermal management and superior optics designed for maximum visual comfort. Simple spring ceiling retention method to suit ceiling thicknesses between 1-50mm. Supplied with connected remote driver. Large round, 165mm diameter cut out, 173mm over bezel. Anti ligature attachment kit 237mm diameter over bezel. Luminaire to be ordered separately Emergency Output:- 8.4w - 41% 16.6w - 20% 26.5w - 12% 35w - 9%


Light output 1




1 x LED			
Nominal lamp power	8.4 W	LOR	103%
Lamp flux	677 lm	Total flux	694 lm
Luminous efficacy	83 lm/W	Total power	8.4 W
CCT	3000 K		
CRI	90		



1 x LED			
Nominal lamp power	16.6 W	LOR	103%
Lamp flux	1628 lm	Total flux	1669 lm
Luminous efficacy	101 lm/W	Total power	16.6 W
CCT	3000 K		
CRI	80		




1 x LED			
Nominal lamp power	26.5 W	LOR	103%
Lamp flux	2449 lm	Total flux	2511 lm
Luminous efficacy	95 lm/W	Total power	26.5 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	35 W
Lamp flux	3187 lm
Luminous efficacy	93 lm/W
CCT	3000 K
CRI	80


LOR	103%
Total flux	3268 lm
Total power	35 W



1 x LED

Nominal lamp power	8.4 W
Lamp flux	880 lm
Luminous efficacy	107 lm/W
CCT	4000 K
CRI	80


LOR	103%
Total flux	902 lm
Total power	8.4 W



1 x LED

Nominal lamp power	16.6 W
Lamp flux	1751 lm
Luminous efficacy	108 lm/W
CCT	4000 K
CRI	80


LOR	103%
Total flux	1795 lm
Total power	16.6 W



1 x LED

Nominal lamp power	8.4 W
Lamp flux	818 lm
Luminous efficacy	100 lm/W
CCT	3000 K
CRI	80


LOR	103%
Total flux	839 lm
Total power	8.4 W



1 x LED


Nominal lamp power	35 W
Lamp flux	3427 lm
Luminous efficacy	100 lm/W
CCT	4000 K
CRI	80

LOR	103%
Total flux	3514 lm
Total power	35 W

**1 x LED**


Nominal lamp power	35 W
Lamp flux	2844 lm
Luminous efficacy	83 lm/W
CCT	4000 K
CRI	90

LOR	103%
Total flux	2916 lm
Total power	35 W

**1 x LED**


Nominal lamp power	16.6 W
Lamp flux	1348 lm
Luminous efficacy	83 lm/W
CCT	3000 K
CRI	90

LOR	103%
Total flux	1382 lm
Total power	16.6 W

**1 x LED**


Nominal lamp power	26.5 W
Lamp flux	2028 lm
Luminous efficacy	78 lm/W
CCT	3000 K
CRI	90

LOR	103%
Total flux	2079 lm
Total power	26.5 W

**1 x LED**


Nominal lamp power	35 W
Lamp flux	2639 lm
Luminous efficacy	77 lm/W
CCT	3000 K
CRI	90

LOR	103%
Total flux	2706 lm
Total power	35 W

**1 x LED**


Nominal lamp power	8.4 W
Lamp flux	730 lm
Luminous efficacy	89 lm/W
CCT	4000 K
CRI	90

LOR	103%
Total flux	749 lm
Total power	8.4 W




1 x LED

Nominal lamp power	16.6 W	LOR	103%
Lamp flux	1453 lm	Total flux	1490 lm
Luminous efficacy	90 lm/W	Total power	16.6 W
CCT	4000 K		
CRI	90		



1 x LED

Nominal lamp power	26.5 W	LOR	103%
Lamp flux	2186 lm	Total flux	2241 lm
Luminous efficacy	85 lm/W	Total power	26.5 W
CCT	4000 K		
CRI	90		



1 x LED

Nominal lamp power	26.5 W	LOR	103%
Lamp flux	2633 lm	Total flux	2700 lm
Luminous efficacy	102 lm/W	Total power	26.5 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.94 in

Diameter: 6.69 in

Adjustability

Fixed

Electric

System power: 8.4-35 W

Protection

IP: 44