Product data sheet

MIRAGE 3 165 ROUND ANTI-LIGATURE MEDIUM WHITE

WHITECROFT









See lamps to select output and colour variants MIRAGE 3 recessed downlighter white reflector, medium distribution. Narrow 11mm width bezel and shallow depth body. Graphite heat sink for optimum thermal management and superior optics designed for maximum visual comfort. Simple spring ceiling retention method to suit ceiling thicknesses between 1-50mm. Supplied with connected remote driver. Large round, 165mm diameter cut out, 173mm over bezel. Anti ligature attachment kit 237mm diameter over bezel. Luminaire to be ordered separately Emergency Output:- 8.4w - 41% 16.6w - 20% 26.5w - 12% 35w - 9%

Light output 1




1 x LED	
Nominal lamp power	8.4 W
Lamp flux	677 lm
Luminous efficacy	83 lm/W
CCT	3000 K
CRI	90

LOR	103%
Total flux	694 lm
Total power	8.4 W



I X LED	
Nominal lamp power	16.6 W
Lamp flux	1628 lm
Luminous efficacy	101 lm/W
CCT	3000 K
CRI	80

LOR	103%
Total flux	1669 lm
Total power	16.6 W




1 x LED			
Nominal lamp power	26.5 W	LOR	103%
Lamp flux	2449 lm	Total flux	2511 lm
Luminous efficacy	95 lm/W	Total power	26.5 W
CCT	3000 K		
CRI	80		

14X) W X X X X X X X X X X X X X X X X X X	1 x LED			
	Nominal lamp power	35 W	LOR	103%
	Lamp flux	3187 lm	Total flux	3268 lm
XXX	Luminous efficacy	93 lm/W	Total power	35 W
	CCT	3000 K		
	CRI	80		
XTTX				
1	1 x LED			
	Nominal lamp power	8.4 W	LOR	103%
	Lamp flux	880 lm	Total flux	902 lm
XXX	Luminous efficacy	107 lm/W	Total power	8.4 W
	CCT	4000 K		
	CRI	80		
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	1 x LED			
	Nominal lamp power	16.6 W	LOR	103%
	Lamp flux	1751 lm	Total flux	1795 lm
	Luminous efficacy	108 lm/W	Total power	16.6 W
	CCT	4000 K		
	CRI	80		
	1 x LED			
	Nominal lamp power	8.4 W	LOR	103%
	Lamp flux	818 lm	Total flux	839 lm
	Luminous efficacy	100 lm/W	Total power	8.4 W
\times	CCT CRI	3000 K 80		
	CRI	80		
K X W X L	1 x LED			
HA HI	Nominal lamp power	35 W	LOR	103%
	Lamp flux	3427 lm	Total flux	3514 lm
	Luminous efficacy	100 lm/W	Total power	35 W
	CCT	4000 K	rotal power	00 VV
\times \times		T000 IX		

80

CRI


1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI	35 W 2844 lm 83 lm/W 4000 K 90	LOR Total flux Total power	103% 2916 lm 35 W
1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI	16.6 W 1348 lm 83 lm/W 3000 K 90	LOR Total flux Total power	103% 1382 lm 16.6 W
1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI	26.5 W 2028 lm 78 lm/W 3000 K 90	LOR Total flux Total power	103% 2079 lm 26.5 W
1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI	35 W 2639 lm 77 lm/W 3000 K 90	LOR Total flux Total power	103% 2706 lm 35 W
1 x LED Nominal lamp power Lamp flux Luminous efficacy CCT CRI	8.4 W 730 lm 89 lm/W 4000 K 90	LOR Total flux Total power	103% 749 lm 8.4 W




CRI

1 x LED			
Nominal lamp power	16.6 W	LOR	103%
Lamp flux	1453 lm	Total flux	1490 lm
Luminous efficacy	90 lm/W	Total power	16.6 W
CCT	4000 K		

90



1 x LED			
Nominal lamp power	26.5 W	LOR	103%
Lamp flux	2186 lm	Total flux	2241 lm
Luminous efficacy	85 lm/W	Total power	26.5 W
CCT	4000 K		
CRI	90		



1 x LED			
Nominal lamp power	26.5 W	LOR	103%
Lamp flux	2633 lm	Total flux	2700 lm
Luminous efficacy	102 lm/W	Total power	26.5 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.94 in Diameter: 6.69 in

Adjustability

Fixed

Electric

System power: 8.4-35 W

Protection

IP: 44