


Product data sheet

STORA-RA 420/4100/830 OS
SPC0620041
RIDI



STORA Anbauleuchte Design: Rundes Leuchtenelement mit einer opalen Acrylglasscheibe in einen Profilrahmen aus pulverbeschichtetem Aluminium eingefasst. Der Rahmen ist durch einen Bajonettverschluss mit Einrastfeder am pulverbeschichteten Blechkörper aus Stahlblech befestigt. Im Blechkörper sind die elektrischen Bauteile und das elektronische Vorschaltgerät eingebaut. Das Leuchtmittel ist als runde LED-Flächenplatine ausgebildet und zur Montage oder zum Austausch über eine Schlüsselloch Schraubverbindung abnehmbar. Der elektrische Anschluss der LED-Flächenplatine erfolgt über eine Steckerverbindung. Die Leuchte ist mit wärmebeständiger Verdrahtung ausgeführt. Homogene Ausleuchtung der Lichtfläche. Für Decken oder Wandmontage geeignet. Lichtfarbe 4000 K. Schutzart IP20, Schutzklasse I. Farbe: Rahmen – ähnl. RAL 9016 Weiß seidenmatt

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	29 W	CRI	80
Total flux	3420 lm	LOR	79%
Luminous efficacy	118 lm/W	ULOR	4%
		Total power	29 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 16.54 in

Width: 16.54 in

Height: 3.07 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 29 W

Appliance Class: I

Protection

IP: 20