


Product data sheet

MICROS-C D95 6/2,3W LED840 700MA SP AL
60813916
ZUMTOBEL



LED ceiling-recessed luminaire (beam angle); lamp(s): 6/2,3 W LED840, colour temperature: neutral white (4000K); Luminaire luminous flux: 714 lm, Luminaire efficacy: 52 lm/W; colour rendering index: RA80; 50,000h service life at 70% luminous flux; spotlight mounting plate is gimbal-mounted for $\pm 20^\circ$ tilt; LED recessed luminaire designed as replacement for 50W low-voltage halogen lamp; die-cast aluminium housing, aluminium ceiling surround in brushed finish; includes 0.62m power lead (halogen-free) with power socket for multiplug system; fixing clips provided for tool-free installation in ceilings of thickness 1-25 mm; ceiling cut-out: $\varnothing 95\text{mm}$, recess depth: 100 mm; weight: 0.32 kg; Please note: please order control gear (700mA) separately as accessory; please also order one extra power lead (60700226) per control gear unit; luminaire can also be operated using 350mA or 500mA control gear, which results in a lower luminaire luminous flux and higher luminaire efficiency.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13.8 W	CRI	99
Total flux	714 lm	LOR	100%
Luminous efficacy	52 lm/W	Total power	13.8 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.35 in
Diameter: 4.13 in
Weight: 0.32 kg

Design

Material impression: Aluminum

Electric

System power: 13.8 W
Appliance Class: III

Protection

IP: 20
Designation labels: CE