


Product data sheet

KUBIK POLE 300 2/2/2/2 LED 1,7W ODB E IP65 22 6500K
19.3161.0018.22
LUXIONA



Outdoor luminaire. Assembly: for the ground. The body material is aluminum. Colour - RAL 9007 (dark gray, metallic, fine structure). Luminaire dimensions: 150 x 150 x 300 mm. Diffuser: transparent polycarbonate. The efficiency of the optical system is 83,51%. Beam angle: asymmetric light distribution. Light source type: LED. Colour of the light 6500 K. SDCM=7. CRI>80. Lifetime of LED sources: 50000 h L70/B50. Luminaire luminous flux: 1149 lm. Power of luminaire: 15 W. Luminaire's light efficiency: 76,6 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosp: >0,5. Circuit load capacity: 37 (B10), 59 (B16), 61 (C10), 89 (C16). Operating temperature range: -25 ÷ 30° C. Protection degree: IP65. Impact resistant: IK09. Protection against electric shock: I.

Light output 1



8 x LED			
Nominal lamp power	1.875 W	LOR	83%
Lamp flux	172 lm	Total flux	1148 lm
Luminous efficacy	92 lm/W	Total power	15 W
CCT	6500 K		
CRI	80		

Mounting mode

Pole integrated

Shape and measurements

Length: 5.91 in
Width: 5.91 in
Height: 11.81 in

Adjustability

Fixed

Design

Color of housing: Anthracite / graphite, Silver gray

Electric

System power: 15 W
Appliance Class: I

Protection

IP: 65
IK: 09

Other operating numbers

Ambient temperature range: -13...86°F