


Product data sheet

CUDDLE MINI LED REG 48 5000K DW
222833/6/DW/10KV
ROSA



One of the most frequently chosen luminaires. The basic version of the product from the CUDDLE MINI LED series. In a compact size, made of aluminium - in the standard version the body is anodised in inox and black. Installed on an extension arm with a \varnothing 60 x 100 mm ending. Most often, it illuminates city and residential streets, pedestrian routes and car parks. It has a protection class of IP 66 for the optical part and the power input system. The luminaire is equipped with PMMA lenses, an interchangeable LED module and a tempered glass diffuser. The expected service life of the product is L90B10 - 100,000. h. The input voltage frequency is 50/60Hz. Power factor ≥ 0.95 . The fixture has 16 LEDs. It is possible to connect the luminaire to an external control system via the DALI interface (optional support for an analogue 1-10V signal).

Light output 1



1 x LED			
Nominal lamp power	54 W	LOR	83%
Lamp flux	9050 lm	ULOR	9%
Luminous efficacy	168 lm/W	Total flux	7503 lm
CCT	5000 K	Total power	54 W
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 28.35 in
Width: 8.11 in
Height: 3.39 in

Adjustability

Free

Electric

System power: 54 W

Protection

IP: 66