# Product data sheet


LED IT STRIP 982520.002



Series: LED IT STRIP Flexible fully encapsulated LED strip for indoor and outdoor use. UV/IR resistant TPU potting. LED Pitch 35.7 mm. Solderless connection technology by means of Plug+Play connector system. No need for silicone sealing. Easy separability with commercially available tools (every 250 mm). Smallest bending radius 60 mm. Up to 20 meters LED strip length with only one power supply. One power feed and one end cap included, other accessories can be ordered separately. Colour: white Length: 5000 mm Width: 12 mm Height: 3.4 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 4 W Rated luminous flux: 370 Im Luminous efficiency: 93 Im/W Protection class: III Type of protection: IP 65

IP 65

### Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	4 W	CRI	80
Total flux	370 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	4 W

#### Mounting mode

Ceiling mounted

## Shape and measurements

Length: 0.47 in Width: 196.85 in Height: 0.12 in

#### Adjustability

Fixed

Electric System power: 4 W Protection IP: 65