Product data sheet

SINUS CURVED SEGMENT FRAME BLACK PRISM. 90° R1440
P33-E59-9005E1940H3M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 40

high output LED 4000K CRI 90 54,6W 6278lm¹ DALI ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 26,4% https://katalog.planlicht.com/en-gb/search?q=sinus%20segment

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.82 W	CRI	90
Total flux	785 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.82 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.82 W	CRI	90
Total flux	785 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.82 W

Light output 3 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.82 W	CRI	90
Total flux	785 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.82 W

Light output 4 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.82 W	CRI	90
Total flux	785 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.82 W

Light output 5 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.82 W	CRI	90
Total flux	785 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.82 W

Light output 6 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.82 W	CRI	90
Total flux	785 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.82 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.82 W	CRI	90
Total flux	785 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.82 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.82 W	CRI	90
Total flux	785 lm	LOR	100%
Luminous efficacy	115 lm/W	Total power	6.82 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 58.39 in
Width: 58.39 in
Height: 3.23 in

Adjustability

Fixed

Electric

System power: 54.6 W

Protection

IP: 40