Product data sheet


RT 44
451174.002.1
RZB



IP 44 IK 03

Series: RT 44 Linear luminaire, can be used as wall and mirror luminaire. Base: aluminium, powder-coated. End caps: plastic (polycarbonate), shock-resistant. Diffuser: plastic (polycarbonate), opal. Suitable for Ceiling mounting, Wall (surface). Can be installed horizontally and vertically. Very easy installation thanks to plug-and-play connector system. With push button switch and Schukoplug socket. Driver integrated. High type of protection: IP44 for use in wet areas. Colour: pure white (RAL 9010) Length: 721 mm Width: 55 mm Height: 87 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 10 W Rated luminous flux: 970 lm Beam angle Down: 180° / 109° Luminous efficiency: 97 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 44

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	10 W	CRI	80
Total flux	970 lm	LOR	67%
Luminous efficacy	97 lm/W	ULOR	14%
		Total power	10 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.17 in
Width: 28.39 in
Height: 3.43 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 10 W

Protection

IP: 44
IK: 03