Product data sheet


NEW TRIA® 75
1007421+1007351
SLV



IP 20


Discover the new generation of our NEW TRIA® recessed ceiling light and configure an individual lighting experience. A modular element is the LED MODULE, which is available with dim-to-warm technology (1800K-3000K) and different beam angles (38°/60°) as a phase variant. The robust design and excellent colour reproduction index CRI>90 ensure exceptional quality. In addition, the NEW TRIA® LED MODULE impresses with its service life of L80B10@50,000h.

Light output 1



1 x LED

Nominal lamp power	1.9 W	LOR	100%
Lamp flux	58 lm	Total flux	58 lm
Luminous efficacy	31 lm/W	Total power	1.9 W
CCT	1800 K		
CRI	90		



1 x LED

Nominal lamp power	10.1 W	LOR	100%
Lamp flux	700 lm	Total flux	700 lm
Luminous efficacy	69 lm/W	Total power	10.1 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 4.33 in
Diameter: 3.66 in
Weight: 0.23 kg

Adjustability

Rotatable, Tiltable

Electric

System power: 1.9-10.1 W
Controller: Dimmable 0..10V
Color adjustable
Appliance Class: II

Protection

IP: 20