



# Product data sheet

LAVANO  
451190.000.1.76  
RZB



Series: Lavano Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz "Luminaire base and end caps: anodised stainless steel, brushed; diffuser:" plastic, opal, allows for brilliant glittering light along the lines of the ellipse. LED lamp and decorative element included. Available Colours: aluminium Type of Installation: Ceiling mounting, Wall (surface) Dimensions: L 860, B 109, H 80 Lamp: LED Life time: 50000 h (L90/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 3800lm System power: 35W Beam Angle: 180°/112° Number of fittings B10A: 10 Number of fittings B16A: 17 Number of fittings C10A: 16 Number of fittings C16A: 26 Inrush current: 49A Unified Glare Ratio: 25,0 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	35 W	CRI	80
Total flux	3800 lm	LOR	100%
Luminous efficacy	109 lm/W	ULOR	47%
		Total power	35 W

## Mounting mode

Wall mounted

## Shape and measurements

Length: 4.29 in  
Width: 33.86 in  
Height: 3.15 in

## Adjustability

Fixed

## Electric

System power: 35 W

## Protection

IP: 40  
IK: 02