Product data sheet

LDRT8B LED 8" ROUND RECESSED RETROFIT DOWNLIGHT LD8B10D010 ER8B10930 8LBSW0MW


COOPER LIGHTING





Retrofit, remodel, install from below, downlight or wall wash, Excellent light control and low aperture brightness, Available for shallow or standard plenums; ENERGY STAR® qualified, Spun aluminum reflectors in a variety of finishes, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W[™] option from 3000K to 1850K, W2N Tunable White 2700K-6500K or 2000K-5000K, Lumens: 1,000-20,000; 0-10V dimming down to 1%, WaveLinx and DLVP connected lighting systems compatibility, 5-year warranty

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	10.2 W	CRI	100
Total flux	932 lm	LOR	100%
Luminous efficacy	91 lm/W	Total power	10.2 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 3.94 in Width: 3.94 in Height: 3.94 in

Adjustability

Fixed

Electric

System power: 10.2 W

Protection

IP: 47