Product data sheet

EVA III 9.751.2056.00

LEIPZIGER LEUCHTEN






CRI




For medium light requirements, mounting height 4.50 - 6.00 m. - Impact-resistant beaded polycarbonate attachment, UV-stabilized - Aluminium reflector finished in special white paint for max. light reflection - Corrosion-resistant cast aluminium unit carrier, painted - All electrical components on a block - Adapter jack for connection - Available in any RAL- or DB - colour without surcharge - For concrete pole with flange plate made of hot galvanized steel Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711

Light output 1



1 x High pressure sodium vapour lamp			
Nominal lamp power	100 W		
Lamp flux	10400 lm		
Luminous efficacy	75 lm/W		
CCT	2000 K		

LOR 83%
ULOR 22%
Total flux 8675 lm
Total power 115 W



1 x High pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	83%
Lamp flux	5600 lm	ULOR	22%
Luminous efficacy	56 lm/W	Total flux	4671 lm
CCT	2000 K	Total power	83 W
CRI	25		

25

Mounting mode

Pole top mounted

Shape and measurements

Height: 17.72 in Diameter: 15.75 in Electric

System power: 83-115 W

Protection

IP: 55