Product data sheet


INFINITE PRO 1136MM SUSPENDED BATWING
AK15-2PW8B2OSN3
LEDSC4



IP 20

LedsC4 Infinite Pro 1136mm Suspended Batwing AK15-2PW8B2OSN3V2 Lineal lighting system for indoor use. For downlighting. Structure finish: Grey. Diffuser material: Polycarbonate. Diffuser finish: Batwing. Warranty: 5 Years. Product net weight (Kg): 2.86 Product length (mm): 1136 Product width or diameter (mm): 52 Product height (mm): 90 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: TRIDONIC. Maximum power of light source: 16.6W. Colour temperature: 3000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 80.000h L80B20. UGR: 19.9. Photobiological risk: RG1. % de Flickering: +/- 5%. Real flux (lm): 2943. Real lm/W: 163. Voltage / frequency range: 220-240/50-60Hz. Voltage: 96. Equipment included: Yes. Total power: 18.1. Power factor: 0.95. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED

Nominal lamp power	18.1 W	LOR	100%
Lamp flux	2943 lm	Total flux	2943 lm
Luminous efficacy	163 lm/W	Total power	18.1 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted, Standing / Bollard

Shape and measurements

Length: 2.05 in
Width: 44.72 in
Height: 3.54 in

Adjustability

Fixed

Electric

System power: 18.1 W
Appliance Class: I

Protection

IP: 20