


Product data sheet

EPF-R1X115-30DA-O
1760027
RIDI




Diffuser luminaire Design: Panel mounting luminaire, protection rating IP 54. Galvanised steel housing with welded and sealed end pieces, white powder coated, colour similar to RAL 9016 with black edging. Durable rubber gasket glued in place and strong diffuser retention clips guarantee a tight diffuser seal. For RIDI-TUBE lamps (order separately). Electronic DALI converter for LED, 230 Volt, 0/50-60 Hz and internal connector block. Mounting: Mounting in 100 x 100 or 200 x 200 modular metal panelled ceilings with the supplied fixing brackets. Not suitable for panelled ceilings with filler strips. EPF-R ... O Opal acrylic diffuser in UV-stabilised PMMA. For lamp RIDI-TUBE, recommended cover: clear.

Light output 1



1 x LED			
Nominal lamp power	21 W	LOR	77%
Lamp flux	3020 lm	Total flux	2339 lm
Luminous efficacy	111 lm/W	Total power	21 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	32 W	LOR	77%
Lamp flux	4780 lm	Total flux	3703 lm
Luminous efficacy	109 lm/W	Total power	34 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 49.09 in
Width: 4.13 in
Height: 3.84 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 21-34 W
Appliance Class: I

Protection

IP: 54