


Product data sheet

GALAXY_CVR_2_57W_NEUTRAL_D1205MM
820921023_
PETRIDIS



GALAXY CVR / GALAXY CVR-D is a 24V DC low voltage aluminium profile. It is an ideal solution for small showcases, homes, rest areas, museums, hotels, exhibition halls and generally for many decorative and architectural projects. Technical Features - Aluminium body, painted electrostatically in selected colour. - Connection for operation with 24V DC. - Pure light without IR/UV radiation. - Efficient thermal management. - Operation life: 50,000 hours with efficiency > 80% of the initial luminous flux (L80B10). Upon Request - Available also in 2700 Kelvin CRI 90.

Light output 1



1 x LED			
Nominal lamp power	57 W	LOR	57%
Lamp flux	7992 lm	Total flux	4521 lm
Luminous efficacy	140 lm/W	Total power	57 W
CCT	4000 K		
CRI	90		

Mounting mode

Pendant

Shape and measurements

Height: 2.17 in
Diameter: 47.44 in

Adjustability

Fixed

Design

Material impression: Aluminum, Chrome, Plastic

Electric

System power: 57 W
Controller: Dimmable 1..10V, DALI
Suitable for feed-through wiring
Appliance Class: III

Protection

IP: 40
Designation labels: CE