


Product data sheet

COMMERCIAL LINEAR - VASCO EVO BLACK 3000K + UGR DIFFUSER
AVAS4/1/B (30W 3000K) + AVAS4/1/UGR
ANSELL LIGHTING



• Aluminium bi-directional suspended or surface linear suitable for education, commercial and retail applications • Bi-directional light output as standard with 30% upward light and 70% downward light ratio (downward only option can be selected if required, please note light output changes in downward only mode) • CCT selectable between 3000K and 4000K and power selectable; offering a choice 2 of outputs, in one luminaire • High efficiency upto 150lm/W (when used with UGR reflector) • Opal diffuser (provided as standard) ensures optimal light uniformity • Innovative lens design with different diffuser options allows end user the choice between standard or low glare UGR<19 rated outputs. Low glare rated diffuser sold separately as accessory (AVAS**/1/UGR) • Integral PIR option discreetly positioned in the end cap • Pre-wired with 1.5 metre cable and supplied with suspension kit with adjustable suspension points • Surface and track mounting available using AVAS/WM/1 and AVAS/P3/1/* accessories • 1-10V dimmable as standard • LED lifespan L80 100,000 hours Operating Temp -20°C to 45°C

Light output 1



1 x LED			
Nominal lamp power	30.2 W	LOR	100%
Lamp flux	4461 lm	ULOR	19%
Luminous efficacy	148 lm/W	Total flux	4461 lm
CCT	3000 K	Total power	30.2 W
CRI	80		

Mounting mode

Pendant

Electric

System power: 30.2 W

Shape and measurements

Length: 47.24 in

Width: 2.17 in

Height: 2.95 in

Protection

Designation labels: CE

Adjustability

Fixed