


# Product data sheet

PLM L30  
PLANUM  
DEXTRA



Planum - 500mm, IP20 Wall mounted luminaire. White powder coated steel body and twin lensed optic for 50% up/down distribution Options: S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function)\* H - High Frequency Dimming (Analogue 1-10v) RAS - Reacta Air Wireless occupancy and daylight dimming RLS - Reacta-Link Wireless Presence & Daylight Sensor RAS sensors can not be offered in PLM and PLMD L12 and L15 variants Additional colour finishes available: BL - Black Finish GY - Grey Finish

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	22.1 W	CRI	80
Total flux	2654 lm	LOR	100%
Luminous efficacy	120 lm/W	ULOR	4%
		Total power	22.1 W

Mounting mode

Wall mounted

Shape and measurements

Length: 19.96 in  
Width: 3.94 in  
Height: 1.46 in

Adjustability

Fixed

Electric

System power: 22.1 W  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

Protection

IP: 20  
Designation labels: CE