


Product data sheet

PENDANT LUMINAIRE DIME OFFICE L4 39W CRI > 80 4000K WHITE D
2003.0910 - DIME PEN1158X366-1525 LED4600-840 DIR WH DALI E3
REGENT



Pendant luminaire Dime Office L4, with LED, system power: 39 W, standby power 0.5 W, luminous flux of luminaire 4600 lm, colour rendering index CRI > 80, colour temperature 4000 K, neutral white, colour tolerances SDCM 2, lifetime LED L80 50'000 h, office-compatible and glare-free according to EN 12464-1 ($UGR < 19$; $L_{max} \geq 65^\circ \leq 3000 \text{ cd/m}^2$), photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, housing in metal, white, 1 integral control gear, DALI, with emergency unit, for non-maintained and maintained mode, with self-test, complete with battery pack, (burning life 3h), Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2021 (Re-0301), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP40, glow wire test 650 °C, impact strength: IK 06, this product contains a light source of energy efficiency class B and EPREL registration number: 1125970 L = 1158 mm, B = 366 mm, H = 25 mm, p = 1525 mm

Light output 1



1 x LED			
Nominal lamp power	43 W	LOR	100%
Lamp flux	4600 lm	Total flux	4602 lm
Luminous efficacy	107 lm/W	Total power	39 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 45.59 in
Width: 14.41 in
Height: 0.98 in
Weight: 7.511 kg

Adjustability

Height adjustable

Design

Color of housing: White

Electric

System power: 39 W
Appliance Class: I

Protection

IP: 40
IK: 06