

Product data sheet

NORA IV (W. SHIELD ON SIDE FACING BUILDING OPAL ATTACHMENT)

9.774.1032.36


LEIPZIGER LEUCHTEN



IP
55

For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection - Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier, painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of delivery includes special steel post/wall-mounted bracket, painted -Order post dia. 60 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x Metal halide lamp

Nominal lamp power	70 W	LOR	84%
Lamp flux	7200 lm	ULOR	3%
Luminous efficacy	68 lm/W	Total flux	6017 lm
CCT	3000 K	Total power	89 W
CRI	90		

Mounting mode

Pole top mounted

Shape and measurements

Height: 11.81 in

Diameter: 21.26 in

Electric

System power: 89 W

Protection

IP: 55