# Product data sheet

161 LED EMERGENCY LIGHT FITTING
161 15L34 110V ZB (16118 0179)
SCHUCH



IP 65 IK 05

LED emergency light fitting, 21 W, 3440 lm, 164 lm/W, Central supply (ZB), Class I, IP65, symmetrical wide beam, 4000 K, CRI≥ 80, Ta -20 °C/+40 °C, L70>100000 h (@ Ta max), L80>70000 h (@ Ta max), L90>50000 h (@ Ta 25°C), Diffuser PMMA satined, Closure Plastic, Housing Glass fibre reinforced polyester, Colour grey. Sturdy LED damp-proof light fitting for connection to group or central battery systems with incorporated fuse for selective disconnection in case of failure. Highly impact-resistant glass fibre reinforced polyester housing and frosted diffuser with high impact resistance. Captive clips, multi-part, incl. two safety clips, silicone gasket. Powder-coated aluminium reflector with highly efficient Zhaga LED modules and ECG with overload and short circuit protection. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 1572,00 mm, Width/Diameter 116,00 mm, Height 125,00 mm, Net weight 2,91 kg.

## Light output 1 (integrated, emergency)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 21 W | CRI | 80 |
| Total flux | 3440 lm | LOR | 100% |
| Luminous efficacy | 164 lm/W | ULOR | 7% |
| | | Total power | 21 W |

## Light output 2 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 4000 K |
| Nominal lamp power | 21 W | CRI | 80 |
| Total flux | 3440 lm | LOR | 100% |
| Luminous efficacy | 164 lm/W | ULOR | 7% |
| | | Total power | 21 W |

### Mounting mode

Ceiling mounted, Pendant, Contact rail, Wall mounted

### Shape and measurements

Length: 61.89 in
Width: 4.57 in
Height: 4.92 in

### Electric

System power: 42 W
Appliance Class: I

### Information regarding emergency functions

Supplementary emergency lighting
Emergency sign: N/A

## Adjustability

Fixed

## Protection

IP: 65

IK: 05

Designation labels: CE