Product data sheet

RECESSED DOWNLIGHT NOVO 2 ROUND INNER RING SET BACK ROUND 13.5W 1500LM CRI > 90 4000K 43MA B 2010.9927 - NOVO2 RD SB CR137 LED1500-940-R27 BK DALI


REGENT



IP 44 IK 07

Recessed downlight Novo 2 Round inner ring set back, with LED, system power: 13.5 W, standby power 0.5 W, luminous flux of luminaire 1500 lm, colour rendering index CRI > 90, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L90 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, rated current: 43 mA, direct light emission, housing in die-cast aluminium, with ceiling trim, black, RAL 9005, with reflector, 27, 1 integral control gear, DALI2, high-quality die-cast aluminium housing, reduced installation time thanks to fully pre-assembled luminaire, including connection to control gear, with through-wiring option, suitable for ceiling thicknesses from 1 to 45 mm protection class II, ingress protection IP20 / IP44, glow wire test 850 °C, impact strength: IK 07 this product contains a light source of energy efficiency class D and EPREL registration number: 2026464 Ø = 153 mm, ceiling cutout ø 137 mm up to 148 mm, ET = 106 mm,

Light output 1



1 x LED

Nominal lamp power	8.2 W	LOR	100%
Lamp flux	1500 lm	Total flux	1500 lm
Luminous efficacy	183 lm/W	Total power	13.5 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 0.04 in
Width: 0.04 in
Height: 0.04 in
Weight: 0.841 kg

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 13.5 W
Appliance Class: II

Protection

IP: 44
IK: 07