
Product data sheet

LUCAS PI (BOLLARD) 9.881.5307.00 LEIPZIGER LEUCHTEN



Decorative luminaire for lanes, driveways, terraces, gardens, and for night illumination and hazardous areas. - Impact-resistant clear/opal polycarbonate cylinder, UV-stabilized - Mirror lamellae for light guidance and glare limitation made of premium highest-grade aluminium, burnished and anodized - Unit carrier, crown flange and ornaments made of corrosion-resistant cast aluminium, painted; ground and passivated special steel parts preferably in jet black, RAL 9005 - Housing/upright tube of special steel painted in any RAL or DB colour without surcharge, or special steel, ground and passivated - All electrical components accommodated on a block -Crown detachable for easy maintenance/lamp change - Upright tube without pole door, incl. adapter jack Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711

Light output 1



1 x Compact fluorescent lamp

IP 55

r x compact nucleocent lump			
Nominal lamp power	18 W	LOR	
Lamp flux	1200 lm	ULOR	
Luminous efficacy	27 lm/W	Total flux	
CCT	2899 K	Total power	
CRI	90		

etric
tem power: 19 W
tection
55
t

Design

Color of housing: Black

43%

17%

521 lm

19 W