

# Product data sheet


GOLAS MIDI  
911400.003.1.76  
RZB



IP  
20

Series: Golas Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Housing: powder coated die cast aluminium. Passive cooling. Rotates 356° horizontally and swivels 65° vertically. Installation without tools thanks to spring fastening system. Heat resistant plastic ring. Reflector: faceted aluminium, included, can be changed without tools. LED included. Connected converter included in separate gearbox. Available Colours: deep black, matt (RAL 9005) Type of Installation: Recessed ceiling mounting Dimensions: D 155, H 4, HE 130 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Luminaire flux LED: 3350lm System power: 36W Beam Angle: 23° Number of fittings B10A: 35 Number of fittings B16A: 55 Inrush current: 20A Unified Glare Ratio: 18,4 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	36 W	CRI	80
Total flux	3350 lm	LOR	100%
Luminous efficacy	93 lm/W	Total power	36 W

## Mounting mode

Ceiling recessed

## Shape and measurements

Height: 0.04 in  
Diameter: 6.10 in

## Adjustability

Rotatable, Tilttable

## Design

Color of housing: Black

## Electric

System power: 36 W

## Protection

IP: 20