


# Product data sheet

SAFESITE LED HIGH BAY 9650 LUMENS, MEDIUM DISTRIBUTION, TEMPERED GLASS LENS  
HEA9MC4DNKCG  
DIALIGHT



Safesite LED High Bay 9,650 Lumens 88 Watts 100-277V AC Cool White, 75CRI Tempered Glass Lens IECEx/ATEX Zones 1, 21 IECEx/ATEX Zones 2, 22 CE ABS Design Assessed: (pending) RoHS Compliant IECEx BAS 10.0074X BaseefaATEX0148X Ex II 2 GD Ex d\* IIB T4 Gb Ex tb IIC 135°C IK10 Medium Distribution IP66

## Light output 1 (integrated)



Lamp type	LED	CCT	5181 K
Nominal lamp power	89.2 W	CRI	75
Total flux	10128 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	89.2 W

## Mounting mode

Pendant

## Shape and measurements

Length: 15.94 in

Width: 15.94 in

Height: 5.04 in

## Adjustability

Rotatable, Tilttable

## Electric

System power: 89.2 W

Voltage: 240 V AC, 120 V AC, 277 V AC, 110 V AC, 230 V AC

Appliance Class: I

## Protection

IP: 66

IK: 10