Product data sheet


POLE MOUNTED LUMINAIRE OSLO 650-2 - WITH LOUVERS ASY33 16LED 2700K
88.02400.0V002
HESS



IP 54


Round luminaire canopy, horizontally split in two, made of aluminium, plain coloured. Support elements made of aluminium, painted. Cylindrical luminaire enclosure made of PC. Round luminaire body made of aluminium with louvres.

Light output 1




1 x LED

Nominal lamp power	22.5 W	LOR	100%
Lamp flux	2482 lm	Total flux	2482 lm
Luminous efficacy	110 lm/W	Total power	22.5 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	33.9 W	LOR	100%
Lamp flux	3711 lm	Total flux	3711 lm
Luminous efficacy	109 lm/W	Total power	33.9 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	31.6 W	LOR	100%
Lamp flux	3473 lm	Total flux	3473 lm
Luminous efficacy	110 lm/W	Total power	31.6 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	29.4 W	LOR	100%
Lamp flux	3232 lm	Total flux	3232 lm
Luminous efficacy	110 lm/W	Total power	29.4 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	24.8 W	LOR	100%
Lamp flux	2737 lm	Total flux	2737 lm
Luminous efficacy	110 lm/W	Total power	24.8 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	20.2 W	LOR	100%
Lamp flux	2222 lm	Total flux	2222 lm
Luminous efficacy	110 lm/W	Total power	20.2 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	1954 lm	Total flux	1954 lm
Luminous efficacy	109 lm/W	Total power	18 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	15.7 W	LOR	100%
Lamp flux	1680 lm	Total flux	1680 lm
Luminous efficacy	107 lm/W	Total power	15.7 W
CCT	2700 K		
CRI	80		




1 x LED

Nominal lamp power	13.4 W	LOR	100%
Lamp flux	1409 lm	Total flux	1409 lm
Luminous efficacy	105 lm/W	Total power	13.4 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	11.1 W	LOR	100%
Lamp flux	1133 lm	Total flux	1133 lm
Luminous efficacy	102 lm/W	Total power	11.1 W
CCT	2700 K		
CRI	80		



1 x LED

Nominal lamp power	27.1 W	LOR	100%
Lamp flux	2986 lm	Total flux	2986 lm
Luminous efficacy	110 lm/W	Total power	27.1 W
CCT	2700 K		
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 25.59 in
Width: 25.59 in
Height: 19.33 in

Adjustability

Fixed

Electric

System power: 11.1-33.9 W

Protection

IP: 54