Product data sheet


FRAME SQUARE MAXI WHITE 2370LM 4000K RA>80 DALI EMERGENCY 3H
7021986053739
SG ARMATUREN



IP 66 IK 10

The Frame light fitting features a modern, stylish design that is great whether it is used indoors or outdoors. It can be mounted on ceilings and walls. Made using pressure-moulded, powder-coated aluminium with a black, white or graphite surface. The shade is produced from UV-stabilised opal polycarbonate. The Frame family is available in round, square and rectangular shapes in a range of sizes. Versions featuring sensors, twilight switches and emergency lights are available. Easy to install, two inputs/outputs for cables, with the option for either hidden or visible cabling. 10 year corrosion guarantee, IP65 protection rating, impact strength IK10. Light distribution Direct Light technic LED (not exchangeable) 21W 4000K Ra>80 SDCM 3 L70/B20 >100,000 hrs L80/B20 >75,000 hrs Control/Dimming DALI Emergency 3H Protection Class II IP66 IK10 Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 31, B16: 50, C10: 52, C16: 85

Light output 1



1 x LED

Nominal lamp power	21 W	LOR	100%
Lamp flux	2370 lm	Total flux	2370 lm
Luminous efficacy	113 lm/W	Total power	21 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 12.20 in
Width: 12.20 in
Height: 3.03 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 21 W
Appliance Class: II

Protection

IP: 66
IK: 10