Product data sheet


TX-MOVE
901727.003.76
RZB



IP 20 IK 03


Series: TX-MOVE Einlege/Einbau-Flächenstrahler. Housing made of sheet steel, powder-coated. Swivel range: 90°. High-efficiency LED units with flush-mounted opal diffuser made of non-yellowing PMMA. Symmetrical wide beam light emission. Suitable for laying in grid ceiling module 600. Connected converter included in separate gearbox. Suitable for through-wiring. MultiLumen: Luminous flux variable in 3 steps. Accessories: Mounting frame for installation in suspended ceilings. Replaceable components make repairs possible and extend the service life. Colour: deep black, matt (RAL 9005) Length: 597 mm Width: 116 mm Height: 39 mm Cut-out length: 577 mm Cut-out width: 98 mm Recess height: 100 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 80 System power: 18 W Rated luminous flux: 2450 lm Beam angle Down: 112° Luminous efficiency: 136 lm/W System power 2: 26 W Rated luminous flux 2: 3350 lm Luminous efficiency 2: 129 lm/W System power 3: 39 W Rated luminous flux 3: 4700 lm Luminous efficiency 3: 121 lm/W Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

Light output 1




1 x LED

Nominal lamp power	26 W	LOR	100%
Lamp flux	3350 lm	ULOR	13%
Luminous efficacy	129 lm/W	Total flux	3350 lm
CCT	3000 K	Total power	26 W
CRI	80		



1 x LED

Nominal lamp power	18 W	LOR	100%
Lamp flux	2450 lm	ULOR	13%
Luminous efficacy	136 lm/W	Total flux	2450 lm
CCT	3000 K	Total power	18 W
CRI	80		



1 x LED

Nominal lamp power	39 W	LOR	100%
Lamp flux	4700 lm	ULOR	13%
Luminous efficacy	121 lm/W	Total flux	4700 lm
CCT	3000 K	Total power	39 W
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.57 in
Width: 23.50 in
Height: 1.54 in

Adjustability

Rotatable, Tiltable

Design

Color of housing: Black

Electric

System power: 18-39 W

Protection

IP: 20
IK: 03