


Product data sheet

LINEAR SURFACE IP44 DALI 600 P 18W 830 WT
4058075733398
LEDVANCE



Robust IP44 luminaires with direct light emission, integrated DALI driver, up to 137 lm/W. Product features: Surface mounted luminaires with direct light emission. Type of protection: IP44. Impact resistance: IK08. Available in 3 different lengths: 600 mm, 1200 mm and 1500 mm. High luminous efficacy: up to 137 lm/W. Through-wiring cable already installed. Lifetime (L80/B10): 70,000 h (at 25 °C). White painted steel housing (like RAL: 9003). Diffuser material: UV-stable polycarbonate. End caps (made of polycarbonate) screwed to the housing. Product benefits: Low maintenance and low operational costs. Protection against cover falling, theft and vandalism thanks to safety screws. Cable entry on the back of the luminaire and on each end-caps for easy electrical connection. Easy and quick installation. Low flicker light thanks to special electronic control gear. 5 years guarantee. Areas of application: Efficient replacement for traditional T8 and T5 luminaires. Public buildings. General illumination. Libraries, schools. Equipment / Accessories: Equipped with through-wiring cables and connectors. Tool-free cable strain reliefs included.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	18 W	CRI	80
Total flux	2340 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	18 W

Mounting mode

Ceiling mounted, Wall mounted

Shape and measurements

Length: 23.94 in
Width: 6.54 in
Height: 2.48 in
Weight: 1.5 kg

Adjustability

Fixed

Design

Material impression: Stainless steel
Color of housing: White

Electric

System power: 18 W
Appliance Class: I

Protection

IP: 44
IK: 08
Designation labels: CE, ENEC

Other operating numbers

Ambient temperature range: -4...104°F